

Presence®

Valueline



*Magnetically Shielded
Orient vertically or horizontally*



CEDIA®

ISO 9002

Lifetime Limited Warranty

HOME THEATER LOUDSPEAKERS

Welcome Home

PV-LCRS

Dual 5 1/4" 2-way rectangular MTM
Poly woofers with butyl surround
Silk soft dome pivoting tweeter
Frequency response: 45 Hz - 20 kHz \pm 4 dB
Power handling: 50 watts nom. 100 max.
Sensitivity: 91dB 1 watt / 1 meter
Impedance: 8 Ohm nominal
Overall dimension: 9" x 15 3/4"
Cut-out: 7 7/8" x 14 7/16" x 3 1/2" deep
Pre-construction bracket: **RIB-LCR**

PV-6LCRS

6 1/2" 2-way round **15° Angled Loudspeaker**
Poly woofers with butyl surround
Pivoting dome tweeter
Frequency response: 45 Hz - 20kHz \pm 4 dB
Power handling: 50 watts nom. 100 max.
Sensitivity: 91dB 1 watt / 1 meter
Impedance: 8 Ohm nominal
Overall dimension: 10 3/4" round
Cut-out: 9 1/4" round x 5" deep
Pre-construction bracket: **RIR-615**
The 15 degree angle enables significantly enhanced cinematic sound imaging when room layouts dictate ceiling mounted loudspeakers

PV-8LCRS

8" 2-way round **15° Angled Loudspeaker**
Poly woofers with butyl surround
Pivoting dome tweeter
Frequency response: 35 Hz - 20 kHz \pm 4 dB
Power handling: 60 watts nom. 120 max.
Sensitivity: 91dB 1 watt / 1 meter
Impedance: 8 Ohm nominal
Overall dimension: 12 7/8" round
Cut-out: 11 1/2" round x 5 3/4" deep
Pre-construction bracket: **RIR-815**
The 15 degree angle enables significantly enhanced cinematic sound imaging when room layouts dictate ceiling mounted loudspeakers

OEM Systems Company, Inc.
740 Freeport Blvd., #106 Sparks, NV 89431-6168
775 355-0405 Fax 775 355-0646
www.presenceloudspeakers.com

Product materials & specifications are subject to change / improvement